

SPECIFICATIONS



SYSTEM CONFIGURATION

	E-615S	E-615SL	E-715S	E-715SR
Intel CPU	Intel® Celeron® J1900 up to 2.4GHz (burst) (Quad-core)		4 th gen Intel desktop processor Celeron® 2.2 GHz Core™ i3 2.4 GHz Core™ i5 2.7 GHz	
Main memory	204Pin DDR3L RAM*1 slot, max 8GB		204Pin DDR3L RAM*2 slots, max. 16GB	
O/S compatibility	Windows 7/ POSReady 7 / Windows 8.1 Industry / Windows 10 IoT Enterprise / Linux Kernel 3.0 or above			
Storage	1 x 2.5" SATA HDD/ SDD			
RAID function	n / a		RAID0/1 (Q87 chipset is required)	
Remote Management	n / a		Intel AMT9.0 (Core™ i5 CPU is required)	

I/O CONNECTIVITY

	E-615S	E-615SL	E-715S	E-715SR
Parallel (option)	1	n/a	1	1
USB2.0	3	3	3	3
USB3.0	1	1	2	2
eSATAp/USB2.0 combo	1	1	1	1
RJ45 COM	4	4	3	3
	All with DC5V/12V output			
Gigabit Ethernet	1	1	1	1
Line out	1	1	1	1
PS/ 2 keyboard	1	n/a	1	1
VGA	1	1	1	1
HDMI	n/a	n/a	1	1
RJ12 cash drawer	1	1	1	1
DC12V out	Dual cash drawer support			
	1	1	1	1
DC in	1	1	1	1
Extension I/O Brick	n/a	n/a	n/a	2*12V P-USB 1*24V P-USB

LCD PANEL

15" LED-backlit display
1024 x 768 (default)
300 cd/m²
Flat Resistive Touch
Projected Capacitive Touch (Anti-glare, optional)

PHYSICAL DIMENSIONS (LXWXD)

Fold-flat:128 x 370 x 336 mm
Low-profile(30-degree):272 x 370 x 235 mm
Upright (60-degree):311 x 370 x 235 mm

POWERING SYSTEM

External DC power adapter. AC90 to 264V full range.
1 x System on/off trigger

SAFETY & ENVIRONMENT

CE / FCC/CB/LVD certificated
0°C to 40°
-25°C to 70°C

Identification readers



ENCORE SERIES



RUGGED TOUCH POS TERMINAL.
DESIGNED FOR HARSH ENVIRONMENTS.

15"